

SOLVENT FREE LIQUID WATERPROOFING ---WITH HIGHEST FIRE RATING IN EUROPE 25

PRIMERS SOLVENT FREE

PRODUCT NAME	DRUM SIZE	COVER RATE
Impermax SF primer	25KG	500GMS PER SQ.M
HUMIDITY PRIMER	5KG	250 GMS PER SQ.M
HUMIDITY PRIMER	18KG	250GMS PER SQ.M
EPOXY 100	15KG	250GMS PER SQ.M
PRIMER GC	15KG	500GMS PER SQ.M
Prim Pu 100(Rayston Prim PU 100)	20KG	250 GMS PER SQ.M

WATERPROOFING SOLVENT FREE

Product Name

Impermax SF	25KG	2.2KG PER SQM
Glass Fibre Reinforcement	150sq.m roll	roll 150 x 1m wide
OR		
Geo max 80 POLYESTER REINFORCEMENT	100 sq.m roll	roll 100m x 1m
SOLVENT	20KG	50 GMS. PER SQM.
	4KG	50GMS. PER SQ.M

READ APPLICATION MANUAL

20 Year Warranty

COVER PER DRUM

50 SQ.M
20 SQ.M
72 SQ.M
60 SQ.M
30 SQ. M
80 SQ.M

APPLICATION USE

OLD BITUMEN ROOFING FELT
DAMP WOOD, DAMP CONCRETE
DAMP WOOD, DAMP CONCRETE
DRY CONCRETE.
WET CONCRETE, WET WOOD
DRY CONCRETE.

25sq.m of 1 layers of 1kg

Base Layer of 1kg then Top Coat of 1kg

150 x 1m wide

EMBEDDED BETWEEN 2 X LAYER OF WATERPROOFING

100 x 1 m wide

Choose either Fibreglass or Polyester as Reinforcement

400 SQ.M PER DRUM

CLEANING AND FOR SOLVENT WIPE

80 SQ.M PER DRUM

CLEANING AND FOR SOLVENT WIPE